

RF750

**STREAMLINE YOUR
WORKFLOW AND
MAXIMIZE EFFICIENCY
WITH UHF TECHNOLOGY
—MADE FOR PM75**



Retail



Industrial Production
Process Control



Logistics /
Warehouse Management



Medical / Pharmacy

Specifications

PHYSICAL CHARACTERISTICS

Dimensions	
Standard	83.05 mm W x 160.5 mm L x 168.25 mm H
Weight	471.6g with standard battery (only RF750)
Power	
Battery	3,250 mAh 3.6V Li-ion, removable
Buttons	Trigger, Power, Trigger Mode, Connection Mode
Standard Communications	USB interface
Power Supply	5V/2A adaptor
Notification	Charging LED, Status LED, Connect-Mode, Trigger-Mode LED, Vibration

PERFORMANCE CHARACTERISTICS

Supported Protocol Standards	EPC Global UHF Class 1 Gen 2 V2 / ISO 18000-63
RFID Engine	Impinj® Indy® R2000

Nominal Read Range 6m (19.69ft)

Fastest Read Rate up to 900 tags per second

Frequency / RF Output EU: 865MHz ~ 868MHz = <30dBm (± 0.3dBm)
US: 902MHz ~ 928MHz = <30dBm (± 0.3dBm)

Memory
RAM 160 KB
ROM 1MB

USER ENVIRONMENT

Operating Temperature -10°C to 50°C

Storage Temperature -40°C to 70°C

Drop 1.5m to concrete

Rain / Dust Proof (Sealing) IP54


WIRELESS

Bluetooth Bluetooth Ver. 4.2 BR/EDR/BLE


NFC Tap-to-Pair

ACCESSORIES

Standard Accessories



Optional Accessories



Corporate Headquarters
Point Mobile Co., Ltd.
pm_sales1@pointmobile.com
+82 2 3397 7870

NA Headquarters
Point Mobile Americas LLC
info@pointmobileamericas.com
+1 425 780 4452

Europe Headquarters
Point Mobile Europe GmbH
europe@pointmobile.com
+49 6196 777 3666

China Headquarters
Point Mobile China
info@pointmobile.com.cn
+86 755 8869 1169

For more information, visit www.pointmobile.com