

1D Handheld Barcode Scanner



XL-6500



- ◎ Self knowledge property right, personalized customization is welcome
- ◎ Support serial port command setting, make the second development convenient
- ◎ Firmware update online with USB cable.
- ◎ Support black and white inverse barcode decode.
- ◎ Aggressive scanning performance on difficult codes. (low print contrast, damaged, fuzzy and long codes)



Light Source	Visible Laser Diode 650nm	Size	L × W × H:175mm × 73mm × 102mm
Scan Pattern	Single Scan	Weight	246g
Decode Rate	300 times/second	Material	ABS+PC
Scan Precision	3mil	Voltage	5VDC
Scan Width	30mm@scan window, 220mm@200mm	Operating Current	85mA
Scan Depth of Field	0-330mm (0.33mm pcs0.9)	Static Current	30mA
Elevation Angle	65	EMC	CE & FCC DOC compliance
Deflection Angle	55	Operating Temperature	- 0°C to 50°C
Support Interface	PS-2(KB); RS-232; USB-HID; USB-Virtual COM	Storage Temperature	- 40°C to 70°C
Print Contrast	10% UPC/EAN 100%	Humidity	5% to 85% relative humidity , non-condensing
Mention Pattern	Buzzer, Indicator	Light Levels	Daylight,3000-8000LUX
Decoding Capability	EAN-8/EAN-13/UPC-A/UPC-E/Code 39/Code 93/Code 128/EAN128/Codaber/Industooal 2 of 5/Interleave 2 of 5/Matrix 2 of 5/MSI.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com