

Wireless Scanner



XL-9310



- ⊙ IP54 & withstand 1.5M drops
- ⊙ 1 base frame can support 99 scanners
- ⊙ Wireless induction charge without cable
- ⊙ One full charge support 100,000 times scan
- ⊙ 600M communication distance on open places
- ⊙ Memory card inserted, can store 100,000 EAN-13 barcode



Light Source	Visible Laser Diode 650m	Size	L × W × H:170mm × 71mm × 98mm
Scan Pattern	Single Scan & Manual	Charge Mode	Induction Charging
Working Frequency	433 MHz ISM frequency	Weight	797.4g
Communication Distance	Up to 600m at open places	Material	ABS+PC
Scan Precision	3mil	Voltage	2200 mAh/DC 5V
Scan Rate	300 times/second	Operating Current	110mA/35mA
Scan Width	30mm@scan window,220mm@200m	EMC	CE & FCC DOC compliance
Depth of Scan Field	0-280mm(0.33mm,PCS=90%)	IP Standard	IP54
Scan Angle	30° & 65° & 55°	Decoding Capability	all 1D barcode including GS1
Support Interface	RS232,PS2 and USB	Humidity	5% to 95% relative humidity
Print Contrast	10% UPC/EAN 100%	Shock	1.5M drops
Decoding Capability	Industrial 2 of 5 /Standard 25/Matrix 25/Code 11/Codabar/MSI/plesseyUK/plessey/Code39 (Standard 39 & Full ASCII Code 39) Code 32/Code 93/Code128/UPCA/UPCE/EAN13/EAN8/UPC/EAN add-on 2/5/ISBN/ISSN/ GS1(RSS) RSS-14/LIMITEDEXPENDED/Include GS1 STACK		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com