

Security LINE EDI10AU

(Linux version)

Rugged Tablet PC

Security LINE
DESIGNED FOR INDUSTRIAL



Ubuntu



IP65



GPS



Dual-battery



Bluetooth



Linux OS
2D



4G



WIFI



Camera

Performance

- Intel Core i5-1235U/i7-1255U processor
- Ubuntu OS and 16GB RAM + 128GB storage
- 10.1 inch IPS Full HD screen with 10-point capacitive touch

Communication

- 2.4G/5.8G Dual band WIFI 6
- High speed 4G LTE
- BT 5.1 fast transmission

Features

- Choose 1 from 4 modules (2D scan engine, RJ45 Gigabit Ethernet, DB9 and USB2.0)
- Support GPS, Glonass, Optional Beidou
- Equipped with multiple accessories, like docking charger, hand-strap, vehicle mount, car charge, carry handle

Reliability

- IP65 Waterproof and Dustproof, Anti-Static
- Vibration & 1.22m drop resistant
- MIL-STD-810G certified

Product Six Views



Specification Parameter

Basic parameters	
Dimension	289.9 x 196.7 x 27.4 mm
Weight	Device unit 1230 g
Device Color	Black
LCD	10.1 inch IPS 16:10, 1200x1920, 700 nits
Touch Panel	10 point G+F+F capacitive touch screen
Camera	Front 2.0MP Rear 8.0MP
I/O	USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, TF Card x 1, HDMI 2.1a Mini x 1, 12PIN Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, DC 19V 3.42A jack *1
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 19V/3.42A
RTC battery	3V/210mAh
Battery	
Capacity	7.4V/700mAh
Type	Built-in Li-polymer battery
Battery	
Capacity	7.4V/5000mAh
Type	Removable Li-polymer battery
Endurance	4.5h (50% volume sounds, 50% screen brightness, 1080P HD video display by default)

Performance parameter	
CPU	Intel Core i5-1235U/i7-1255U
OS	Ubuntu22.04.4
RAM	16GB
Storage	128GB
Network connections	
WIFI	Wi-Fi 6 802.11a,b,d,e,g,h,i,k,n,r,u,v,w,ac,ax (2.4G+5.8G)
Bluetooth	BT5.1 Transmission distance: 10 m
4G (Optional)	LTE FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B40 WCDMA: B1/B5/B8 GSM: 900/1800
GNSS	Support GPS, Glonass, Optional Beidou
Reliability	
Operate Temperature	-20 °C ~ 60 °C
Store Temperature	-30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP65 certified, MIL-STD-810G certified
Drop Height	1.22m drop
Electrostatic Discharge	± 8kV contact discharge, ± 15kV air discharge
Extension modules (1 out of 4)	
Ethernet interface	RJ45 (10/100/1000M) x 1, (Standard)
Serial port	DB9 (RS232) x 1
USB2.0	USB 2.0 x 1
2D	Optical resolution: 5mil/scan speed: 50 times/s

Accessories



Docking Charger



Hand-strap



Vehicle Mount



Carry handle



Quad charging



Removable Battery

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.



Outdoor Exploration



Manufacturing Industry



Finance



Animal Husbandry